

DEALER HOT WATER PRESSURE WASHERS

Heater Module

Diesel/Oil-Heated | HHM Series



This heater module can convert your cold water pressure washer into a hot water unit whenever you need it. Featuring a powder coated steel frame assembly and several fuel burner options.



HHM-3506-0E10

Frame

- Wrinkle-finish powder coated steel frame assembly
- Stainless-steel coil wrap
- 13-inch flat-free tires

Components

- No. 1 or No. 2 fuel oil, diesel or kerosene fired burner (Not approved for bio-fuel)
- Horizontal schedule 80 pipe coil heat exchanger
- 35-foot power cord with GFCI
- Adjustable thermostat

Miscellaneous

- 250°F maximum outlet temperature (150°F temperature rise at 4.0-GPM)

Unit Includes:

- 12-foot x 3/8-inch jumper hose to hook up to existing pressure washer



Model Number	PSI	GPM	Electrical Voltage/Phase/Amp	Burner Fuel Consumption	Diesel BTU per hour	Dimensions (LxWxH)	Ship Wt.	Net Wt.
HHM-3506-0E10	3500	6.0	115V, 1Ø, 3.2A	2.76 gph	386,400	56.5x30x41.5in.	543 lb.	423 lb.

Option:

Part Number	Description	Fits Model
HX-0171	Skid feet - Stationary applications	HHM-3506-0E10

Accessories:

Part Number	Description	Fits Model
50-0170	Stack adapter - Allows 8-inch flue pipe to be installed to boiler exhaust port	HHM-3506-0E10
850-0324	Gasket (for 50-0170) - Seals between 50-0170 stack adapter and boiler housing	HHM-3506-0E10

WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov