

# DEALER HOT WATER PRESSURE WASHERS

## Portable Electric

### Direct Drive | DHS Series



*This electric pressure washer is built for industrial cleaning where proper ventilation may not be accessible. It features a top-fired heat exchanger that is completely accessible.*



DH-2003-SE0E2G

#### Pump

- Direct drive triplex piston General or Mi-T-M pump with ceramic plungers
- Stainless-steel and brass unloader
- Forged brass manifold
- Thermal relief valve
- High pressure detergent injector  
(Available as an option on SE0E1M and SE0E2M models)

#### Motor

- Totally enclosed fan-cooled electric motor with manual thermal overload protection
- 35-foot power cord

#### Components

- Energy-efficient top-fired heat exchanger designed for convenient troubleshooting and easy maintenance
- No. 1 or No. 2 diesel or kerosene fired burner  
(Not approved for bio-fuel)

#### Frame

- Reinforced powder coated steel tube frame with center balanced lift
- 13-inch flat-free tires

#### Miscellaneous

- Temperature rise 150°F/66°C above ambient, maximum outlet temperature is 200°F

#### Unit Includes:

- Quick connect nozzles – 0°, 15°, 25° and 40°
- 50-foot x 3/8-inch steel wire-braided high pressure hose
- Adjustable pressure insulated dual lance
- Professional-grade insulated trigger gun with safety lock-off

#### Mi-T-M Pressure Relief Start:

- Equipped with the Mi-T-M Pressure Relief Start (SE0E1M and SE0E2M models) which eliminates pressure build up in the system. No need to trigger the gun when starting the pressure washer.



# DEALER HOT WATER PRESSURE WASHERS

## Portable Electric

### Direct Drive | DHS Series



| Model Number   | PSI  | GPM | Horsepower/Motor        | Pump    | Plug Type  | Burner Fuel Tank Capacity | Burner Fuel Consumption | BTU per hour | Dimensions (LxWxH) | Ship Wt. | Net Wt. |
|----------------|------|-----|-------------------------|---------|------------|---------------------------|-------------------------|--------------|--------------------|----------|---------|
| DH-1002-SE0E1G | 1000 | 2.0 | 1.5 HP, 120V, 1Ø, 15.0A | General | NEMA 5-15P | 4.0 gallons               | 1.33 gph                | 186,000      | 43x29.5x36.5in.    | 418 lb.  | 295 lb. |
| DH-1002-SE0E1M | 1000 | 2.0 | 1.5 HP, 120V, 1Ø, 15.0A | Mi-T-M  | NEMA 5-15P | 4.0 gallons               | 1.33 gph                | 186,000      | 43x29.5x36.5in.    | 410 lb.  | 237 lb. |
| DH-1502-SE0E1G | 1500 | 2.0 | 2.0 HP, 120V, 1Ø, 19.0A | General | NEMA 5-20P | 4.0 gallons               | 1.21 gph                | 169,000      | 43x29.5x36.5in.    | 422 lb.  | 299 lb. |
| DH-1502-SE0E1M | 1500 | 2.0 | 2.0 HP, 120V, 1Ø, 19.0A | Mi-T-M  | NEMA 5-20P | 4.0 gallons               | 1.21 gph                | 169,000      | 43x29.5x36.5in.    | 414 lb.  | 291 lb. |
| DH-2003-SE0E2G | 2000 | 2.8 | 4.0 HP, 230V, 1Ø, 18.0A | General | NEMA 6-20P | 4.0 gallons               | 1.48 gph                | 207,200      | 43x29.5x36.5in.    | 439 lb.  | 316 lb. |
| DH-2003-SE0E2M | 2000 | 2.8 | 4.0 HP, 230V, 1Ø, 18.0A | Mi-T-M  | NEMA 6-20P | 4.0 gallons               | 1.48 gph                | 207,200      | 43x29.5x36.5in.    | 431 lb.  | 308 lb. |

| Options:    |  |                 |
|-------------|--|-----------------|
| Part Number | Description  | Fits Models     |
| HX-0232     | <b>300°F steam</b> - Reduces pressure to 350-PSI by adjusting unloader valve counter-clockwise, spray temperatures will rise 240°F above ambient with a maximum of 300°F | DH-1002-SE0E1G  |
| HX-0233     | <b>Adjustable thermostat</b> - Operator is able to adjust outlet water temperature between 86°-248°F   | All models      |
| HX-0235     | <b>Hour meter</b> - Displays number of hours unit has been in operation  | All models      |
| HX-0237     | <b>Auto start/stop</b> - When trigger gun is released, the timer will turn unit off; when trigger gun is pulled, unit will restart                                       | DH-1002-SE0E1M  |
| HX-0238     | <b>Time delay shutdown</b> - Timer will shut unit off automatically when trigger gun is released and timer reaches setting   | DH-1002-SE0E1M  |
| HX-0239     | <b>300°F steam</b> - Reduces pressure to 350-PSI by adjusting unloader valve counter-clockwise, spray temperatures will rise 240°F above ambient with a maximum of 300°F | DH-1002-SE0E1M  |
| HX-0240     | <b>300°F steam</b> - Reduces pressure to 350-PSI by adjusting unloader valve counter-clockwise, spray temperatures will rise 240°F above ambient with a maximum of 300°F | DH-2003-SE0E2G  |
| HX-0241     | <b>300°F steam</b> - Reduces pressure to 350-PSI by adjusting unloader valve counter-clockwise, spray temperatures will rise 240°F above ambient with a maximum of 300°F | DH-2003-SE0E2M  |
| HX-0243     | <b>Auto start/stop</b> - When trigger gun is released, the timer will turn unit off; when trigger gun is pulled, unit will restart                                       | 2000-PSI models |
| HX-0244     | <b>Time delay shutdown</b> - Timer will shut unit off automatically when trigger gun is released and timer reaches setting   | 2000-PSI models |
| HX-0245     | <b>300°F steam</b> - Reduces pressure to 350-PSI by adjusting unloader valve counter-clockwise, spray temperatures will rise 240°F above ambient with a maximum of 300°F | DH-1502-SE0E1M  |
| HX-0246     | <b>300°F steam</b> - Reduces pressure to 350-PSI by adjusting unloader valve counter-clockwise, spray temperatures will rise 240°F above ambient with a maximum of 300°F | DH-1502-SE0E1G  |
| HX-0275     | <b>Auto start/stop</b> - When trigger gun is released, the timer will turn unit off; when trigger gun is pulled, unit will restart                                       | DH-1502-SE0E1M  |
| HX-0276     | <b>Time delay shutdown</b> - Timer will shut unit off automatically when trigger gun is released and timer reaches setting   | DH-1502-SE0E1M  |

| Accessories: |  |             |
|--------------|--|-------------|
| Part Number  | Description  | Fits Models |
| 50-0161      | <b>High pressure detergent injector</b> - High pressure water mixes with detergent to clean even the heaviest build-up | All models  |
| 850-0433     | <b>50-ft. x 3/8-inch high pressure hose</b> - For when you need extra hose for added mobility                          | All models  |



NEMA 5-15P,  
15-amp plug



NEMA 5-20P,  
20-amp plug



NEMA 6-20P,  
20-amp plug

**WARNING:** Cancer and Reproductive Harm - [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).